



単位：mm

| 呼び径 | 止め輪 寸法 | | | | | | | | | |
|-----|----------------|-----------|------|------|----|-----|---------------------------|-----|-------|-------|
| | d ₃ | | b | | t | | d ₀ +0.5 -0 | E±2 | (H±2) | R MAX |
| | 寸法 | 公差 | 寸法 | 公差 | 寸法 | 公差 | | | | |
| 105 | 98.8 | 0 -1.4 | 8.0 | | | | 3.5 | | 18 | |
| 110 | 103.8 | | | | | | | | | |
| 115 | 108.8 | | | | | | | | | |
| 120 | 113.8 | | | | | | | | | |
| 125 | 118.7 | | | | | | | | | |
| 130 | 123.7 | 0 -2.5 | | | | | 4.0 | | 20 | 1.2 |
| 135 | 128.7 | | | | | | | | | |
| 140 | 133.7 | | | | | | | | | |
| 145 | 138.7 | | | | | | | | | |
| 150 | 142.7 | | | | | | | | | |
| 155 | 146.7 | | | | | | | | | |
| 160 | 151.7 | | | | | | | | | |
| 165 | 156.2 | 0 -3.0 | 12.0 | ±0.2 | | 4.0 | ±0.09 | 8 | | |
| 170 | 161.2 | | | | | | | | | |
| 175 | 166.2 | | | | | | | | | |
| 180 | 171.2 | | | | | | | | | |
| 185 | 176.2 | | | | | | | | | |
| 190 | 181.1 | | | | | | | | | |
| 200 | 191.1 | | | | | | | | | |
| 210 | 199.5 | | | | | | | | | |
| 220 | 209.5 | | | | | | | | | |
| 230 | 219.5 | | | | | | | | | |
| 240 | 229.5 | | | | | | | | | |
| 250 | 239.5 | | | | | | | | | |
| 260 | 246.5 | | | | | | | | | |
| 270 | 256.5 | | | | | | | | | |
| 280 | 266.5 | | | | | | | | | |
| 290 | 276.5 | | | | | | | | | |
| 300 | 286.5 | | | | | | | | | |

※弊社品番：04070- (例)呼び105の場合 04070-00105